

## PRODUCT DATA SHEET

Standing: 2021-07-21

### LAUDA ECO ET 15 S

Heating thermostat 230 V; 50/60 Hz

Part Number: L001098

#### Features

- Thermostatic bath/circulator with latest microprocessor technology
- Monochrome graphic LCD display for simultaneous indication of actual and set value
- User friendly menu navigation in plain language
- Easy input via cursor and soft keys. Additional Tmax key for overtemperature protection
- Fully electronic continuous controller with PID action
- Safety class III for operation with flammable and non-flammable liquids. Over-temperature cut-out adjustable via menu
- Vario pump with six adjustable performance levels
- Easy control of the flow rate between internal and external circulation during operation without contact with the bath
- USB interface as standard
- Upgradeable with an interface module (analogue module, contact module, RS 232/485 module, Profibus, Ethernet-USB module)
- Upgradeable with Pt 100/LiBus module for external control and remote control via Command console
- Integrated programmer, 1 programme with max. 20 segments
- Pump connectors with plastic nipples 13 mm as standard
- Transparent bath made from polycarbonate



Reserve technical changes



Working temperature min.  
20 °C



Working temperature max.  
100 °C

## PRODUCT DATA SHEET

Standing: 2021-07-21

LAUDA ECO ET 15 S

Heating thermostat 230 V; 50/60 Hz

Part Number: L001098

### Technical Features

Working temperature range	20 ... 100 °C
Ambient temperature range	5 ... 40 °C
Temperature stability	0.01 ± K
Heater power max.	2 kW
Power consumption max.	2.1 kW
Power consumption	10 A
Pump Pressure max.	0.6 bar
Pump flow rate pressure max.	22 L/min
Bath volume min. / max.	13.5 / 15.0 L
Size of bath (W x D x H)	275 x 130 x 310 mm
Overall dimensions (WxDxH)	428 x 148 x 532 mm
Power supply	230 V; 50/60 Hz
Power plug	Power cord with angled plug (CEE7/7)


## PRODUCT DATA SHEET

Standing: 2021-07-21

LAUDA ECO ET 15 S

Heating thermostat 230 V; 50/60 Hz

Part Number: L001098



Reserve technical changes