




Scanning Stage SCAN^{plus} IM 130 \times 85 for Nikon Eclipse Ti

Specifications

Travel range	max. 130 × 85 mm
Travel speed	max. 120 mm/s (with 2 mm ball screw pitch)
Repeatability	< 1 µm¹ (bi-directional)
Accuracy	±1 μm¹
Resolution	0.05 μm (smallest step size)
Orthogonality	< 10 arcsec
Motor type	2-phase stepper motor
Limit switches	wear-free Hall sensors
Material / surface	aluminium / anodic coating, black lacquered
Weight	approx. 6.8 kg



Order Information

Order No.: 00-24-626-0000 (2 mm ball screw pitch)

Product Features

- integrated linear measuring systems for highest accuracy
- flat, ergonomic design with rounded corners
- plain surface for easy cleaning
- stationary connecting cables between scanning stage and controller
- integrated electronic stage identification device ETS for automatic identification of the scanning stage and parametrization of the controller
- 5 years guarantee, if the scanning stage is operated in the system with the Märzhäuser TANGO controller

Accessories

Stage insert for 1 slide 3" × 1" (included in delivery) Order No.: 00-29-411-8010

Piezo Z-stage Order No.: 00-55-550-0800

For various stage inserts with dimensions $160 \times 110 \times 8$ mm and further accessories please visit: <u>www.marzhauser.com</u>

