

## PRODUCT DATA SHEET

Standing: 2021-07-20

LAUDA Proline PV 15

Clear-view thermostat 230 V; 50/60 Hz

Part Number: L001532

### Features

- Thermostatic bath/circulator with latest microprocessor technology and installed cooling coil
- Easily readable green LED display for temperature
- User-friendly menu guidance with simplest 3-key operation
- EasyUse system for simple operation of the whole unit
- SelfCheck Assistant for system diagnosis
- Fully electronic continuous controller with PID action for internal & external control
- PowerAdapt system for the use of the maximum possible amount of heat permitted by the power supply system
- Low-level and adjustable over-temperature protection with acoustic alarm for use with flammable and non-flammable liquids
- LAUDA Varioflex pump (pressure) with 8 selectable levels
- Option for upgrading with up to 2 interfaces (RS 232/485, Profibus, analogue or contact modules, Ethernet-USB module)
- Measuring chamber with big windows front and back
- Pump connectors on the side and in the back, installed bypass
- Bath vessel made of stainless steel (insulated, with handles and drain tap)



Working temperature min.  
30 °C



Working temperature max.  
230 °C

Reserve technical changes



## PRODUCT DATA SHEET

Standing: 2021-07-20

LAUDA Proline PV 15

Clear-view thermostat 230 V; 50/60 Hz

Part Number: L001532

### Technical Features (according to DIN 12876)

Working temperature range	30 ... 230 °C
Working temperature range with external cooling	20 ... 230 °C
Operating temperature range	0 ... 230 °C
Ambient temperature range	5 ... 40 °C
Temperature stability	0.01 ± K
Heater power max.	3.6 kW
Power consumption	16 A
Power consumption max.	3.7 kW
Pump Pressure max.	0.8 bar
Pump flow rate pressure max.	25 L/min
Bath volume min. / max.	11.0 / 15.0 L
Size of bath (W x D x H)	230 x 135 x 320 mm
Overall dimensions (WxDxH)	506 x 282 x 590 mm
Power supply	230 V; 50/60 Hz
Power plug	Power cord with angled plug (CEE7/7)

### Standard accessories

- 4 screw caps, 4 closing plugs
- 2 nipples 13 mm for pump connectors
- 2 nipples for cooling coil

Reserve technical changes




## PRODUCT DATA SHEET

Standing: 2021-07-20

LAUDA Proline PV 15

Clear-view thermostat 230 V; 50/60 Hz

Part Number: L001532



Reserve technical changes



## PRODUCT DATA SHEET

Standing: 2021-07-20

LAUDA Proline PV 15

Clear-view thermostat 230 V; 50/60 Hz

Part Number: L001532

