UNICHROMAT-Model year 2011

Special Chromatography Cabinet for Äkta-Systems from GE-HEALTHCARE

UNICHROMAT 1500

Mod. 2011 with more power: 1744W

New isolation: 80mm



UNICHROMAT 1500 for the Äkta System

- Left chamber: Shelve for the Äkta system max 100kg,

2x power socket

- Right chamber: 3x shelve, max. 20kg, 2x power socket

In the middle: 2x support system for columns.



- Available volumes: 700 / 1500 /1700/2100 liters
- Interior made of stainless steel
- White housing, powder coated
- Digital temperature control with visual alarm
- Digital display in 0,5°C
- Potential-free outlet for connection to a house alarm system,
- Over-temperature protection
- Under temperature safety device with own sensor
- The humidity control is based on the evaporator fan functioning according to the compressor working status.
- CFC/HCFC free cooling system, fully hermetically sealed and with forced ventilation, mounted on anti-vibration damper, smooth running and low noise emission
- Working temperature: +4°C constant with amplified cooling performance, for compensating the heating emission of the Äkta-System
- Regulation from +1°C to +18°C
- PT-100 temperature control sensor
- Adjustable shelves of stainless steel
- Fully insulated safety-glass doors, self-closing, large glass area for best viewing conditions
- Fully-automatic defroster
- 2x moisture-proofed internal electrical sockets in each chamber
- 2x access ports 40mm left & right
- Illumination
- Double blower for air circulation
- Condensate removal system
- Evaporator is mounted outside of the chamber on top against electromagnetic interference of the Äkta
- Wheels with breaks + 1x adjustable foot=1500/1700/2100
- 4 x adjustable foot=Unichromat 700
- Power 220V / 50Hz
- Lock included

Specifically designed for the Äkta-System from GE Healthcare:

- Telescopic-shelves, placed according to user's needs
- Retractable over telescopic rails
- Maximum loading capacity 100kg

Accessories:

- Additional moisture-proofed plugs
- Additional shelves
- Retractable drawers
- Chromatography-column holder
- Data logger with alarm and software
- Models 1500 without middle-column for big instruments
- Twin Compressor for 2x ÄKTA System (2x1700W)
- Special UNICHROMAT for the Äkta AVANT System (Unichromat1700)

UNICHROMAT-1500







UNICHROMAT-700



Unichromat 700
for the ÄKTA System
-Shelve for the Äkta
System
-4x Power Socket
-1x Support System
for columns

Model	UNICHROMAT 700	UNICHROMAT 1500	UNICHROMAT 2100
Dimensions, mm (WxDxH)			
external dimensions	780x 840x 2100	1560x 840x 2020	2250x 840x 2020
internal dimensions	600x 670x 1510	1350x 670x 1520	2050x 670x 1520
No. of shelves	3 (without Äkta shelve) 0 (with Äkta shelve)	6 (without Äkta shelve) 3 (with Äkta shelve)	9 (without Äkta shelve) 6 (with Äkta shelve)
WxD, shelve	525x490 mm	525x490 mm	525x490 mm
WxD, Äkta sliding support	550x560 mm	550x560 mm	550x560 mm
No. of glass doors	1	2	3
Weight, net	150 kg	250 kg	350 kg
Temperature range	+1°C bis +18°C	+1°C bis +18°C	+1°C bis +18°C
Power	850W	1744W	2407W
Refrigerant	R 404 A (0.35 kg)	R 404 A (0.40 kg)	R 404 A (0.55 kg)