

One Click® Titration Simple and Secure



One Click® User Interface

The large color touchscreen features the simple-to-understand and fast-to-operate One Click user interface. All users have their own homescreen with dedicated shortcut buttons to directly start specific routine tasks.




Compact and simple automation

The automatic Rondolino titration stand is simple to install and takes up minimal bench space. Series of up to 9 samples are processed quickly and safely. Dip-rinsing after each analysis ensures minimal carryover and, after the series, the sensor is moved to a fixed conditioning beaker.



Flexible Data Export

METTLER TOLEDO Compact Titrators offer a broad range of options for handling your data. Choose whether to export as CSV, PDF or XML files. Devices such as printers or memory sticks can be connected via the USB port and are automatically recognized.



LabX® Titration PC software

Full control of the titrator, secure database archiving, networking, efficient result management with control charts and individual search filters, and rapid and clear method development are only a few aspects of the powerful LabX Titration PC software.



G20S Compact Titrator

The Routine Potentiometric G20S titrator combines fast and precise potentiometric titration analysis with simple operation. With its easy-to-use interface and space saving design, it is the optimal choice for your daily routine analysis.

- Color touchscreen with One Click user interface
- User interface in English, German, French, Spanish, Italian, Chinese, Russian, Polish, Korean and Portuguese
- Intelligent burettes with RFID chip saving all relevant titrant data
- Connectivity to LabX Titration PC software
- Common USB printers or the USB-P25 compact printer for secure and GLP-compliant paper recording
- Compact and simple automation

Functionality Overview		G20S
One Click® Titration	User specific Homescreen with Shortcuts	•
	Shortcuts per user	12
Hot Plug and Play	Plug & Play sensor recognition	•
	Burette recognition with titrant and titer	•
	Burette drive	•
	Solvent Manager	•
	USB printer	•
Automation	Memory stick	•
	Rondolino automated titration stand	•
	Max. number to dose and titrate	1 (internal)
Burette drives	Max. number to dose only	1 (internal) + 1 external
	Number of method functions per method	12
	Number of samples per series	120
	Predefined METTLER TOLEDO methods	>20
Methods and series	Max. number of methods	100
Online help		•
Data Export/Printing	USB, Ethernet, PDF	•
PC software	LabX® Titration connectivity: Express	•
Languages	English / German / French / Spanish / Italian / Chinese / Russian / Polish / Korean / Portuguese	
Communication	Ethernet (TCP/IP)	1
	COM (serial balance connection)	1
	USB host (printer, memory stick, hub)	2
	USB client (PC)	1
	TTL I/O	1
	Pump / Stirrer	1

Technical Specifications

Potentiometric sensor input	Measuring range	± 2000 mV
	Resolution	0.1 mV
	Error limit	0.2 mV
Polarized sensor input	Measuring range I _{pol} / U _{pol}	0 ... 2000 mV / 0 ... 200 µA
	Resolution I _{pol} / U _{pol}	0.1 mV / 0.1 µA
	Error limit I _{pol} / U _{pol}	2 mV / 0.2 µA
	Current source range I _{pol} / U _{pol}	0 – 24 µA AC / 0 – 2000 mV AC
	Current source resolution I _{pol} / U _{pol}	0.1 µA / 0.1 mV
PT1000 temperature sensor	Measuring range	–20 ... 130 °C
	Resolution	0.1 °C
	Error limit	0.2 °C
Burette drives	Burette resolution	1/20'000 of the burette volume
	Burette resolution (20mL burette)	1 µL
	Error limit	0.2% of the burette volume
	Resolver resolution	0.0625% of the burette volume
	Fill and eject time	20 s
Titration dimensions	Width x depth x height	210 x 333 x 320 mm
	Weight	4.2 kg
	Screen	VGA 5.7" color TFT
	Resolution	640 x 480 pixels

